

What is claimed is:

Sub
P1

1. A sensor comprising:
 a column bus;
 a column of pixels;
 a first plurality of switches, each switch being coupled between the column bus and a corresponding pixel of the column of pixels;
 a column of accumulators;
 a second plurality of switches, each switch being coupled between the column bus and a corresponding accumulator of the column of accumulators;
 a main control circuit to control the first and second plurality of switches to couple a signal from a pixel of the column of pixels to an accumulator of the column of accumulators while updating the accumulator.

2. The sensor of claim 1, wherein the main control circuit includes:
 a first switch control circuit to control a switch of the first plurality of switches to connect the signal from the pixel of the column of pixels to the column bus while controlling all remaining switches of the first plurality of switches to isolate the column bus from all remaining pixels of the column of pixels; and
 a second switch control circuit to control a switch of the second plurality of switches to connect the signal on the column bus to the accumulator of the column of accumulators while controlling all remaining switches of the second plurality of switches to isolate the column bus from all remaining accumulators of the column of accumulators.

3. The sensor of claim 2, wherein the main control circuit further includes:
 a first increment control circuit to increment the first switch control circuit to control a next in succession switch of the first plurality of switches to connect a signal from a next in succession pixel of the column of pixels to the column bus while controlling all remaining switches of the first plurality of switches to isolate the column bus from all remaining pixels of the column of pixels; and

650F60" FEE6E60

ent cont
sion sw
to a n
all rema
l remain
aim 3,
l circu
ement
it, and t
operation
column
operation
column
aim 4, w
bl circu
ates the
ne colum
ates the
gnal on
of accu
aim 5, w
operate
each tim

- each repetitive operation of the second switch control circuit couples the signal that was coupled onto the column bus from a pixel to a corresponding accumulator of the column of accumulators.

- repetitively operates the second increment control circuit and the second switch control circuit until the signal on the column bus has been successively coupled into all accumulators of the column of accumulators.

6. The sensor of claim 5, wherein the main control circuit further includes a second repeat control circuit to operate the first increment control circuit and then operate the first repeat control circuit each time the second repeat control circuit is operated.

7. The sensor of claim 6, wherein the main control circuit operates the second repeat control circuit each time a point in a moving image projected on the column of pixels transverses a pixel boundary.

8. The sensor of claim 7, wherein the main control circuit repetitively operates the second repeat control circuit until the point in the moving image traverses the column of pixels.

9. The sensor of claim 1 further comprising:

an output bus;

a third plurality of switches, each switch being coupled between the output bus and a corresponding accumulator of the column of accumulators, wherein the main control circuit controls the third plurality of switches to couple an accumulated signal from an accumulator of the column of accumulators to the output bus.

10. The sensor of claim 9, wherein the main control circuit includes a switch control circuit to control a switch of the third plurality of switches to connect the accumulated signal from the accumulator of the column of accumulators to the output bus while controlling all remaining switches of the third plurality of switches to isolate the output bus from all remaining accumulators of the column of accumulators.

11. The sensor of claim 10, wherein the main control circuit further includes an increment control circuit to increment the switch control circuit to control a next in succession switch of the third plurality of switches to connect the accumulated signal at a next in succession accumulator of the column of accumulators to the output bus to while controlling all remaining switches of the third plurality of switches to isolate the output bus from all remaining accumulators of the column of accumulators.

12. The sensor of claim 11, wherein:

003334-091099
660660-TEEE60

13. The sensor of claim 12, wherein each time the repeat control circuit is operated, the repeat control circuit repetitively operates the increment control circuit and the switch control circuit until all accumulators of the column of accumulators have been successively coupled onto the output bus.

15. The sensor of claim 14, wherein the main control circuit repetitively operates the repeat control circuit until the point in the moving image traverses the column of pixels.

an output bus;

17. The sensor of claim 16, wherein the main control circuit includes a third switch control circuit to control a switch of the third plurality of switches to connect the accumulated signal from the accumulator of the column of accumulators to the output bus while controlling all remaining switches of the third plurality of switches to isolate the output bus from all remaining accumulators of the column of accumulators.

18. The sensor of claim 17, wherein the main control circuit further includes a third increment control circuit to increment the third switch control circuit to control a next in succession switch of the third plurality of switches to connect the accumulated signal at a next in succession accumulator of the column of accumulators to the output bus while controlling all remaining switches of the third plurality of switches to isolate the output bus from all remaining accumulators of the column of accumulators.

19. The sensor of claim 18, wherein:
the second repeat control circuit repetitively operates the third increment control circuit and the third switch control circuit; and
each repetitive operation of the third switch control circuit couples a signal from a successive accumulator of the column of accumulators.

20. The sensor of claim 19, wherein each time the second repeat control circuit is operated, the second repeat control circuit repetitively operates the third increment control circuit and the third switch control circuit until all accumulators of the column of accumulators have been successively coupled onto the output bus.

21. The sensor of claim 20, wherein the main control circuit operates the second repeat control circuit each time a point in a moving image projected on the column of pixels transverses a pixel boundary.

22. The sensor of claim 21, wherein the main control circuit repetitively operates the second repeat control circuit until the point in the moving image traverses the column of pixels.

23. The sensor of claim 1, wherein the column bus, all pixels in the column of pixels, a switches of the first and second plurality of switches, all accumulators in the column of accumulators, and the main control circuit include poly-crystalline silicon

650160-11111111

conductors, all poly-crystalline silicon conductors being formed from only a single layer of a patterned poly-crystalline silicon film.

24. A method of scanning an image comprising steps of:
 updating a column of accumulators from a column of pixels by repeatedly incrementing first and second switch control circuits; and
 incrementing the first switch control circuit and a third switch control circuit to output an accumulated value from the column of accumulators.

25. The method of claim 24, wherein the step of updating a column of accumulators includes steps of:

transferring a pixel signal from a pixel selected from the column of pixels based on the first switch control circuit into an accumulator selected from the column of accumulators based on the second switch control circuit; and
 updating the selected accumulator.

26. The method of claim 25, wherein the step of updating a column of accumulators further includes:

a step of causing the step of transferring a pixel signal from a pixel to successively repeat; and

a step of causing the step of updating the selected accumulator to successively repeat to update each accumulator in the column of accumulators.

27. The method of claim 25, wherein the step of transferring a pixel signal includes:

addressing the selected pixel based on the first switch control circuit to transfer a selected pixel signal from the selected pixel onto a column bus; and

addressing the selected accumulator based on the second switch control circuit to transfer the selected pixel signal from the column bus into the selected accumulator.

28. The method of claim 27, wherein the step of updating the selected accumulator includes updating an accumulator signal value stored in the selected accumulator based on the selected pixel signal.

29. The method of claim 24, further comprising a step of causing the steps of updating a column of accumulators and incrementing the first switch control circuit and a third switch control circuit to output an accumulated value to successively repeat.

30. The method of claim 24, wherein the step of incrementing the first switch control circuit and a third switch control circuit to output an accumulated value includes transferring the accumulated value from an accumulator selected from the column of accumulators based on the third switch control circuit onto an output bus.

31. A sensor comprising:
 means for updating a column of accumulators from a column of pixels by repeatedly incrementing first and second switch control circuits; and
 means for incrementing the first switch control circuit and a third switch control circuit to output an accumulated value from the column of accumulators.

32. The sensor of claim 31, wherein the means for updating a column of accumulators includes:
 means for transferring a pixel signal from a pixel selected from the column of pixels based on the first switch control circuit into an accumulator selected from the column of accumulators based on the second switch control circuit; and
 means for updating the selected accumulator.

33. The sensor of claim 32, wherein the means for updating a column of accumulators further includes:
 means for causing the means for transferring a pixel signal from a pixel to successively repeat; and

660760-1EE660

means for causing the means for updating the selected accumulator to successively repeat to update each accumulator in the column of accumulators.

34. The sensor of claim 32, wherein the means for transferring a pixel signal includes:

means for addressing the selected pixel based on the first switch control circuit to transfer a selected pixel signal from the selected pixel onto a column bus; and

means for addressing the selected accumulator based on the second switch control circuit to transfer the selected pixel signal from the column bus into the selected accumulator.

35. The sensor of claim 34, wherein the means for updating the selected accumulator includes means for updating an accumulator signal value stored in the selected accumulator based on the selected pixel signal.

36. The sensor of claim 31, further comprising means for causing the steps of updating a column of accumulators and incrementing the first switch control circuit and a third switch control circuit to output an accumulated value to successively repeat.

37. The sensor of claim 31, wherein the means for incrementing the first switch control circuit and a third switch control circuit to output an accumulated value includes means for transferring the accumulated value from an accumulator selected from the column of accumulators based on the third switch control circuit onto an output bus.

093341-0109
650760-1EE60